



熱收縮套管

功能特性

● 合格認證

FZ : UL , UL 224 , 105 °C , 600 V , VW - 1

F32 : UL , UL 224 , 125 °C , 600 V , VW - 1

CSA C 22.2 , 125 °C , 600 V , VW - 1

● 環保熱收縮套管

功用 : 1. 電線之保護與絕緣

2. 端子與電線接頭之絕緣與保護

3. 分色作用

4. 防水

5. 電阻電容器之保護與絕緣



電器規格說明

型號	收縮前		收縮後		包裝
	內徑mm	厚度mm	內徑mm	厚度mm	
125°C UL CSA					
F32-1	1.3 ± 0.2	0.2	0.5	0.33	每捲 200M
F32-1.5	2.0 ± 0.2	0.2	0.75	0.36	每捲 200M
F32-2	2.5 ± 0.2	0.2	1.0	0.44	每捲 200M
F32-2.5	3.0 ± 0.2	0.2	1.25	0.44	每捲 200M
F32-3	3.5 ± 0.3	0.25	1.5	0.44	每捲 200M
F32-3.5	4.0 ± 0.3	0.25	1.75	0.44	每捲 200M
F32-4	4.5 ± 0.3	0.25	2.0	0.44	每捲 200M
F32-5	5.4 ± 0.3	0.25	2.5	0.56	每捲 100M
F32-6	6.4 ± 0.4	0.25	3.0	0.56	每捲 100M
F32-7	7.4 ± 0.4	0.25	3.5	0.56	每捲 50M
F32-8	8.4 ± 0.4	0.25	4.0	0.56	每捲 50M
F32-9	9.4 ± 0.4	0.25	4.5	0.56	每捲 50M
F32-10	10.4 ± 0.4	0.25	5.0	0.56	每捲 50M
F32-11	11.4 ± 0.4	0.25	5.5	0.56	每捲 50M
F32-12	12.4 ± 0.4	0.25	6.0	0.56	每捲 50M
F32-13	13.5 ± 0.4	0.30	6.5	0.69	每捲 50M
F32-14	14.5 ± 0.4	0.30	7.0	0.69	每捲 50M
F32-15	15.5 ± 0.5	0.30	7.5	0.69	每捲 50M
F32-16	16.8 ± 0.5	0.30	8.0	0.69	每捲 50M
F32-18	18.7 ± 0.5	0.35	9.0	0.77	每捲 50M
F32-20	21.2 ± 0.6	0.35	10.0	0.77	每捲 50M
F32-22	23.2 ± 0.6	0.40	11.0	0.77	每捲 50M
F32-25	26.1 ± 0.8	0.40	12.5	0.87	每捲 50M
F32-28	29.5 ± 1.0	0.45	14.0	0.87	每捲 50M
F32-30	32.0 ± 1.0	0.5	15.0	0.87	每捲 50M

型號	收縮前		收縮後		包裝
	內徑mm	厚度mm	內徑mm	厚度mm	
125°C UL					
FZ-35	37.0 ± 1.0	0.5	17.5	0.87	每捲 50M
FZ-40	43.0 ± 1.5	0.5	20.0	0.97	每捲 50M
FZ-50	53.0 ± 2.0	0.5	25.0	0.97	每捲 50M
FZ-60	60 min.	0.55	30.0	1.07	每捲 50M
FZ-80	80 min.	0.6	40.0	1.07	每捲 50M
FZ-100	100 min.	0.6	50.0	1.07	每捲 30M