




## 粘式束線帶固定座

### 功能特性

- 材質：UL 合格之 NYLON 66 (本色)，防火等級 94 V - 2
- 用法：使用時將底面膠帶撕去離行紙，再將固定座貼於鐵板之上復以紮線帶穿於孔中，即可使用，可省去面板鑽孔之麻煩



### 電器規格說明



型號	長 L	寬 W	高 H	螺絲孔	紮線帶穿孔 T	包裝
HC-101S	19	19	3.9	3.2	4.5	每包100pcs
HC-101	21	21	3.5	-	4.1	每包100pcs
HC-102	28	28	5.3	5.0	5.0	每包100pcs
HC-103	28	28	5.4	5.0	5.0	每包100pcs

適用之紮線帶規格：

HC-101：CV-075, CV-094, CV-100, CV-120, CV-120S, CV-140S, CV-140, CV-150, CV-165, CV-180, CV-200M, CV-200S, CV-250M, CV-292, CV-368S

HC-102：CV-075, CV-094, CV-100, CV-120, CV-120S, CV-120L, CV-140S, CV-140, CV-150, CV-160L, CV-165, CV-180, CV-190, CV-190, CV-200, CV-200M, CV-250, CV-280, CV-310, CV-368, CV-385, CV-432

HC-103：CV-075, CV-094, CV-100, CV-120, CV-150, CV-180, CV-200, CV-200S, CV-250, CV-200M, CV-280, CV-292, CV-310, CV-368, CV-368S, CV-385, CV-432