



固定釘

功能特性

- 採 PE (灰色) 射出成型彈性大、耐衝擊、絕不破裂
均為插釘式，鋼釘直接附著於塑膠座上，
可大量節省工時，降低施工成本



電器規格說明

型號	寬度mm	外高mm	內高mm	適用電線電纜	鋼釘	包裝
NT-1(0N)	4.8	7	2.5	圓0.2mm ² 2C、4C電話線(電信局用)	2.0 × 15	100 pcs
NC-0.275N	2.75	4.5	2.6		1.65 × 19	
NC-0.35N	3.5	5.9	3.7		2.0 × 15	
NC-0.4N	4	6.6	4.2	電信局用新式一對通信電纜	2.5 × 18	
NC-0.5N	5	7.6	5.3	3C2V天線、5對通信電纜、RG-58U	2.5 × 18	
NC-0.5NS					2.0 × 20	
NC-0.5NB(黑色)					2.5 × 18	
NC-1NS	6	9	6.6	5C2V天線、10對通信電纜、 RG-59 U、RG-62U	2.0 × 20	
NC-1N					2.5 × 18	
NC-1NB(黑色)					2.5 × 18	
NC-1NL					10.5	
NC-1.5N	7	11	7.2		2.5 × 22	
NC-1.5 NB(黑色)					2.5 × 22	
NC-2N	8	11.5	8.6	3C 1.25mm ² 電纜、RG-5U、RG-6U	2.5 × 22	
NC-2NS					2.0 × 25	
NC-2.5N					2.5 × 22	
NC-2.5NS					9	
NC-3N	10	13.4	10.5	3C 3.5mm ² 、3C 2mm ² 電纜 20 對通信電纜、RG-8U - 12U	2.5 × 25	
NC-3NS					2.0 × 25	
NC-3.5N	11	16.6	12.2	3C 3.5mm ² 、2C 5.5mm ² 電纜	2.5 × 27	
NC-4N	12	16.0	12.5	2C 5.5mm ² 、3C 3.5mm ² 、4C 5.5mm ² 、電纜	2.5 × 27	
NC-6N	14	20.5	15.6	3C 8mm ² 、電纜	3.0 × 35	
NC-7N	16	21.7	17.0	3C 14mm ² 電纜、3分管、3/8" PVC 管	3.2 × 38	
NC-7.2N	18	22.0	17.5		3.2 × 38	
NC-7.5N	20	23.5	18.5		3.2 × 38	
NC-8N	22	27.8	22.5	3C 22mm ² 電纜、4分管、1/2" PVC 管	3.2 × 42	
NC-9N	25	31.6	26.0	3C 38mm ² 電纜、6分管、3/4" PVC 管	3.2 × 47	
NC-10N	32	40	3.5	1吋管、1" PVC 管	3.2 × 56	50 pcs
NF-1.6 (白扁線)	8.0	8	5.0	1.6mm 白扁線	2.0 × 15	100 pcs
NF-2.0 (白扁線)	8.5	8	5.2	2.0mm 白扁線	2.5 × 18	